

# Extending JuMP and MathOptInterface

---

Benoît Legat (UCLouvain)

August 7, 2019

Extending MathOptInterface

Dualization extension

Extending JuMP

Polyhedra extension

Sum-of-Squares extension

Set Programming extension

ParameterJuMP extension

StructJuMP extension

MomentOpt extension

## Extending MathOptInterface

---

# MathOptInterface (MOI)

- `add_variable(model),`  
`add_constrained_variable(model, set).`
- `add_constraint(model, func, set),` e.g.  $2x + 3y = 1 \rightarrow$   
`(2*x + 3*y)-in-EqualTo(1.0).`
- `set, get` attributes, e.g., `ObjectiveFunction`.
- `submit` submittables, e.g., `HeuristicSolution`.

Extensible framework:

- **Generic** on attribute, function and set types. New ones can be defined **independently**.
- Solver-**specific** features easily exposed to JuMP/MOI users through **custom** attributes, e.g. solver specific callbacks.
- Expose **specialized** problem structure easily through **custom** functions, sets (e.g. Sum-of-Squares variables/constraints).

# Semidefinite programming

$$\begin{array}{ll} \underset{Q \in \mathcal{S}^n}{\text{minimize}} & \langle C, Q \rangle \\ \text{subject to} & \langle A_i, Q \rangle = b_i \\ & Q \succeq 0 \end{array} \qquad \begin{array}{ll} \underset{y \in \mathbb{R}^n}{\text{maximize}} & \langle b, y \rangle \\ \text{subject to} & \sum_i A_i y_i \preceq C \end{array}$$


**File format:** SDPA

**Solvers:** CSDP, SDPA, DSDP, SDPLR, ...

**Variables:**  $Q$  block diagonal, nonnegative scalar variables ( $1 \times 1$  blocks) or SDP matrices.

**Constraints:** Affine equations.

# Interval constraint for SDPA



# Bridges directed hypergraph

## Nodes

Node for each set  $S$  (variable-in- $S$ ).

Node for each constraint  $F$ -in- $S$ .

Node for each objective function  $F$ .

## Edges

For each edge and ingoing node: outgoing nodes are

- variable-in- $S$  created.
- constraints  $F$ -in- $S$  created.
- objective  $F$  set.

# Bridges selection

## Multiple dispatch ?

Can we use multiple dispatch where node types are method signatures ?

**No.** Several bridge can transform same types. Dispatching on more specialized is not accurate.

Need to guide choice to supported types.

## Just in Time (JIT) bridge selection

Types  $F$  and  $S$  are **not limited** to those defined in MOI → **infinitely** many nodes.

Each bridge defined possible **infinitely** many edges.

Need to be **lazy** and compute bridge selection JIT when type first used.

# Bridge selection algorithm

**Data:** Set of bridges  $B$

**Invariant:**  $d_v, d_c, d_o$  are correct when defined.

Given new type: compute types  $T$  where  $d$  should be defined with Depth First Search (DFS) from the type:  $\mathcal{O}(|B|)$ .

Compute  $d$  at the types using Bellman-Ford algorithm:  $\mathcal{O}(|T| \cdot |B|)$ .

## Dualization extension

---

Extends MOI by creating a new **layer**.

Problem given to GLPK is the **dual** of problem given to optimizer.

```
optimizer = Dualization.DualOptimizer(GLPK.Optimizer())
```

*# or*

```
model = Model(with_optimizer(() ->  
    Dualization.DualOptimizer(GLPK.Optimizer())))
```

Primal (resp. dual) results of optimizer are dual (resp. primal) results of GLPK.

```

struct DualOptimizer{T, OT <: MOI.ModelLike} <:
    MOI.AbstractOptimizer
    dual_problem::DualProblem{T, OT}
end
struct DualProblem{T, OT <: MOI.ModelLike}
    dual_model::OT
    primal_dual_map::PrimalDualMap{T}
end
function MOI.copy_to(dest::DualOptimizer,
                    src::MOI.ModelLike; kws...)
    dualize(src, dest.dual_problem)
    # ...
end

```

## Extending JuMP

---

## Extending JuMP macros

```
@constraint(model, [x + 1, x - y] in MOI.Zeros())
```

Implementation:

```
function build_constraint(  
    _error::Function,  
    func::Vector, set::MOI.AbstractVectorSet)  
    return VectorConstraint(x, set)  
end  
function add_constraint(model, c::AbstractConstraint,  
                        name)  
    index = MOI.add_constraint(backend(model),  
                               moi_function(c), moi_set(c))  
    ... # set name and shape  
    return ConstraintRef(model, index, shape(c))  
end
```

## Extending JuMP macros: Custom set

```
@constraint(model, [x + 1, x - y] in SecondOrderCone())
```

Implementation:

```
function build_constraint(_error::Function,  
                        f::AbstractVector,  
                        s::AbstractVectorSet)  
    set = moi_set(s, length(f))  
    return build_constraint(_error, f, set)  
end  
function moi_set(::SecondOrderCone, dim::Int)  
    return MOI.SecondOrderCone(dim)  
end
```

## Extending JuMP macros: PSD cone

```
using LinearAlgebra # For Symmetric
@constraint(model, Symmetric([x + 1 x - y
                             x - y y]) in PSDCone())
```

Implementation:

```
function build_constraint(_error::Function,
                        Q::Symmetric,
                        ::PSDCone)
    n = LinearAlgebra.checksquare(Q)
    func = [Q[i, j] for j in 1:n for i in 1:j]
    set = MOI.PositiveSemidefiniteConeTriangle(n)
    VectorConstraint(func, set,
                    SymmetricMatrixShape(n))
end
```

## Adding bridges

```
struct BridgeableConstraint{C, B} <: AbstractConstraint
  constraint::C
  bridge_type::B
end

function add_constraint(model::Model,
                       c::BridgeableConstraint,
                       name::String="")
  add_bridge(model, c.bridge_type)
  return add_constraint(model, c.constraint, name)
end
```

# Polyhedra extension

---

## Polyhedra example

Creating the hypercube from JuMP:

```
model = Model()  
@variable(model, 0 <= x[1:n] <= 1)
```

```
poly = polyhedron(model, CDDLib.Library(:exact))
```

Polyhedra constraint:

```
simplex = intersect(  
    HalfSpace([-1, 0], 0), HalfSpace([0, -1], 0),  
    HyperPlane([1, 1], 1))  
model = Model()  
@variable(model, x[1:2])  
@constraint(model, A * x in simplex)
```

## JuMP model to polyhedron

```
MOI.Utilities.@model(_MOIModel,  
    (), (MOI.EqualTo, MOI.LessThan,), (), (),  
    (), (MOI.ScalarAffineFunction,), (), ())  
mutable struct LPHRep{T} <: HRepresentation{T}  
    model::_MOIModel{T}  
    # Cached list of indices  
    hyperplane_indices::Union{  
        Nothing, Vector{MOI.ConstraintIndex{  
            MOI.ScalarAffineFunction{T}, MOI.EqualTo{T}}}}}  
    hyperplane_indices::Union{  
        Nothing, Vector{MOI.ConstraintIndex{  
            MOI.ScalarAffineFunction{T}, MOI.LessThan{T}}}}}  
end
```

## Polyhedra constraint: Extending MOI

```
struct PolyhedraOptSet{T, RepT <: Rep{T}} <:  
    MOI.AbstractVectorSet  
    rep::RepT  
end  
struct PolyhedraToLPBridge{T, F} <:  
    MOI.Bridges.AbstractBridge  
    hyperplanes::Vector{MOI.ConstraintIndex{  
        F, MOI.EqualTo{T}}}  
    halfspaces::Vector{MOI.ConstraintIndex{  
        F, MOI.LessThan{T}}}  
end
```

## Polyhedra constraint: Extending JuMP

```
function JuMP.build_constraint(  
    error_fun::Function, func, set::Polyhedra.Rep)  
    return JuMP.BridgeableConstraint(  
        JuMP.build_constraint(  
            error_fun, func, PolyhedraOptSet(set)),  
        PolyhedraToLPBridge)  
end
```

## Sum-of-Squares extension

---

# Nonnegative quadratic forms into sum of squares

$$(x_1, x_2, x_3) \quad p(x) = x^T Q x \quad \text{unique}$$

$$x_1^2 + 2x_1x_2 + 5x_2^2 + 4x_2x_3 + x_3^2 = x^T \begin{pmatrix} 1 & 1 & 0 \\ 1 & 5 & 2 \\ 0 & 2 & 1 \end{pmatrix} x$$

$$p(x) \geq 0 \quad \forall x \iff Q \geq 0 \quad \downarrow \text{cholesky}$$

$$(x_1 + x_2)^2 + (2x_2 + x_3)^2 \longleftarrow x^T \begin{pmatrix} 1 & 1 & 0 \\ 0 & 2 & 1 \end{pmatrix}^T \begin{pmatrix} 1 & 1 & 0 \\ 0 & 2 & 1 \end{pmatrix} x$$

# Nonnegative polynomial into sum of squares

$$(x_1, x_2, x_3) \quad (x_1, x_1 x_2, x_2) \quad \text{not unique}$$

$$p(x) = X^T Q X$$

$$x_1^2 + 2x_1^2 x_2 + 5x_1^2 x_2^2 + 4x_1 x_2^2 + x_2^2 = X^T \begin{pmatrix} 1 & 1 & 0 \\ 1 & 5 & 2 \\ 0 & 2 & 1 \end{pmatrix} X$$

$$p(x) \geq 0 \quad \forall x \iff Q \geq 0 \quad \downarrow \text{cholesky}$$

$$(x_1 + x_1 x_2)^2 + (2x_1 x_2 + x_2)^2 \longleftarrow X^T \begin{pmatrix} 1 & 1 & 0 \\ 0 & 2 & 1 \end{pmatrix}^T \begin{pmatrix} 1 & 1 & 0 \\ 0 & 2 & 1 \end{pmatrix} X$$

# When is nonnegativity equivalent to sum of squares ?

Determining whether a polynomial is nonnegative is **NP-hard**.

## Hilbert 1888

Nonnegativity of  $p(x)$  of  $n$  variables and degree  $2d$  is equivalent to sum of squares in the following three cases:


- $n = 1$  : Univariate polynomials
- $2d = 2$  : Quadratic polynomials
- $n = 2, 2d = 4$  : Bivariate quartics

## Motzkin 1967

First **explicit** example:

$$x_1^4 x_2^2 + x_1^2 x_2^4 + 1 - 3x_1^2 x_2^2 \geq 0 \quad \forall x$$

but is **not** a sum of squares.



# Theory behind bridges

$$\begin{array}{ll} x \in S_1 \Leftrightarrow Ax \in S_2 & AS_1 = S_2 \\ A^*y \in S_1^* \Leftrightarrow y \in S_2^* & S_1^* = A^*S_2^* \end{array}$$

In Lagrangian:

$$\langle Ax, y \rangle_2 = \langle x, A^*y \rangle_1$$

**Transformation of variable-in- $S_2$  to variable-in- $S_1$ .**

Primal Transform value  $v$  to  $Av$ .

Dual Transform dual  $y$  to  $A^{-*}y$ .

**Transformation of  $f$ -in- $S_1$  constraint to  $Af$ -in- $S_2$  constraint.**

Primal Transform value  $v$  of  $Af$  to  $A^{-1}v$  of  $f$ .

Dual Transform dual  $y$  of  $A^*y$ .

## Sum-of-Squares bridges

Polynomial  $p \in \Sigma$  ( $p$  is SOS) iff  $p = X^T Q X$  with  $Q \in \mathbb{S}_+$  ( $Q$  is PSD). Hence  $\Sigma = A\mathbb{S}_+$ .

SOSPolynomialBridge: Transformation of variable-in- $\Sigma$  to variable-in- $\mathbb{S}_+$ .

Transformation of constraint  $F$ -in- $\Sigma$ : SlackBridge + SOSPolynomialBridge.

## Constraint Attribute

**Examples:** ConstraintPrimal, ConstraintDual, ConstraintFunction, ConstraintSet, ...

**Redirected** to bridge when constraint is bridged.

New attributes:

- GramMatrixAttribute: Gram matrix  $Q$  indexed by  $X$ .
- MomentMatrixAttribute: Moment matrix index by  $X$ , dual of constraint  $Q \in \mathbb{S}_+$ .
- MomentsAttribute: Vector of moments, dual of constraint  $p = X^\top QX$ .

## Sum-of-Squares constraint macro

```
@constraint(model, p in SOS Cone())
```

Implementation:

```
function JuMP.build_constraint(_error::Function, p,  
                              cone::SOS Cone; kws...)
    coefs = coefficients(p)
    monos = monomials(p)
    set = JuMP.moi_set(cone, monos; kws...)
    shape = PolyJuMP.PolynomialShape(monos)
    return PolyJuMP.bridgeable(  
        JuMP.VectorConstraint(coefs, set, shape),  
        JuMP.moi_function_type(typeof(coefs)),  
        typeof(set)  
    )
end
```

## Set Programming extension

---

## Example with ellipsoids: Model


Maximal volume ellipsoid (determinant):

```
model = Model(...)
@variable(model, S, Ellipsoid(symmetric=true))
@constraint(model, S ⊆ □)
@constraint(model, A * S ⊆ E * S)
@objective(model, Max, nth_root(volume(S)))
@time JuMP.optimize!(model)
ell = JuMP.value(S)
```


Maximal sum of the squares of the semi-axes of the ellipsoid (trace):

```
@objective(model, Max,
            L1_heuristic(volume(S), [1.0, 1.0]))
```

## Example with ellipsoids: Primal Solution



## Example with ellipsoids: Polar Solution



## Set variables

```
function JuMP.build_variable(  
    _error, info::JuMP.VariableInfo,  
    set::AbstractSetVariable)  
    if info.has_lb || info.has_ub || ...  
        _error(...)   
    end  
    return set  
end  
  
function JuMP.add_variable(  
    model::JuMP.AbstractModel, set::AbstractSetVariable,  
    name::String)  
    vref = SetVariableRef(...)   
    push!(data(model).variables, vref)  
    return vref  
end
```

# Parsing set constraints

```
function JuMP.parse_one_operator_constraint(_error::Function, vectorized::Bool,  
                                           ::Val{:<}, lhs, rhs)  
    _error("Unrecognized symbol < you mean ≤ ?")  
end  
function JuMP.parse_one_operator_constraint(_error::Function, vectorized::Bool,  
                                           ::Val{:<}, lhs, rhs)  
    parse_code = :()  
    if vectorized  
        build_call = :(JuMP.build_constraint($_error, $(esc(lhs)), $(esc(:(SetProg.PowerSet($rhs))))))  
    else  
        build_call = :(JuMP.build_constraint($_error, $(esc(lhs)), $(esc(:(SetProg.PowerSet($rhs))))))  
    end  
    return parse_code, build_call  
end  
function JuMP.parse_one_operator_constraint(_error::Function, vectorized::Bool,  
                                           ::Val{>}, lhs, rhs)  
    _error("Unrecognized symbol >, did you mean ≥ ?")  
end  
function JuMP.parse_one_operator_constraint(_error::Function, vectorized::Bool,  
                                           ::Val{>}, lhs, rhs)  
    parse_one_operator_constraint(_error, vectorized, Val{<}, rhs, lhs)  
end
```

## Store set constraints

```
function JuMP.build_constraint(  
    _error::Function, subset, sup_powerset::PowerSet;  
    kws...)   
    InclusionConstraint(subset, sup_powerset.set, kws)  
end  
  
function JuMP.add_constraint(  
    model::JuMP.Model, constraint::SetConstraint,  
    name::String="")  
    d = data(model)  
    index = ConstraintIndex(d.last_index += 1)  
    d.constraints[index] = constraint  
    d.names[index] = name  
    return JuMP.ConstraintRef(model, index, SetShape())  
end
```

## Optimize hook

create\_spaces: Find dimensions and representation (e.g. polar/dual or not)

```
function optimize_hook(model::JuMP.AbstractModel; kws...)
    d = data(model)
    clear_spaces(d)
    create_spaces(d)
    load(model, d)
    JuMP.optimize!(model, ignore_optimize_hook = true,
                    kws...)
end
```

## ParameterJuMP extension

---

## ParameterJuMP example

```
model = ModelWithParams(with_optimizer(...))  
@variable(model, x)  
add_parameter(model, a, 10)  
@constraint(model, x >= a)  
optimize!(model)  
dual(a)  
  
fix(a, 20)  
optimize!(model)
```

## Adding parametrized constraint

```
function JuMP.build_constraint(  
    _error::Function, aff::PAE, set)  
    return JuMP.ScalarConstraint(aff, set) # Simplified  
end
```

```
function JuMP.add_constraint(model::JuMP.Model, c::PAEC,  
                             name::String="")  
    c_lin = JuMP.ScalarConstraint(c.func.v, c.set)  
    cref = JuMP.add_constraint(model, c_lin, name)  
    data = model.ext[:params]::ParameterData  
    _get_param_dict(data, S)[cref] = c.func.p  
    return cref  
end
```

## Optimize hook

```
function parameter_optimizehook(model::JuMP.Model;  
                                kwargs...)
    data = model.ext[:params]::ParameterData

    sync(data)

    ret = JuMP.optimize!(
        model, ignore_optimize_hook = true, kwargs...)

    if !no_duals(data) && JuMP.has_duals(model)
        _update_duals(data)
    end
    return ret
end
```

## StructJuMP extension

---

## Example

```
numScen = 2
m = StructuredModel(num_scenarios=numScen)
@variable(m, x[1:2])
@NLconstraint(m, x[1] + x[2] == 100)
@NLobjective(m, Min, x[1]^2 + x[2]^2 + x[1]*x[2])

for i in 1:numScen
    b1 = StructuredModel(parent=m, id=i)
    @variable(b1, y[1:2])
    @NLconstraint(b1, x[1] + y[1] + y[2] >= 0)
    @NLconstraint(b1, x[2] + y[1] + y[2] <= 50)
    @NLobjective(b1, Min, y[1]^2 + y[2]^2 + y[1]*y[2])
end
```

## AbstractModel without any MOI backend

```
mutable struct StructuredModel <: JuMP.AbstractModel
    parent::Union{StructuredModel, Nothing}
    # Graph data ...

    nextvaridx::Int
    variables::Dict{Int, JuMP.AbstractVariable}
    varnames::Dict{Int, String}
    nextconidx::Int
    constraints::Dict{Int, JuMP.AbstractConstraint}
    connames::Dict{Int, String}
    objective_sense::MOI.OptimizationSense
    objective_function::JuMP.AbstractJuMPScalar
end
```

# Variables

```
struct StructuredVariableRef <: JuMP.AbstractVariableRef
    model::StructuredModel
    idx::Int
end

function JuMP.add_variable(
    model::StructuredModel, v::JuMP.AbstractVariable,
    name::String="")
    model.nextvaridx += 1
    vref = StructuredVariableRef(
        model, model.nextvaridx)
    model.variables[vref.idx] = v
    JuMP.set_name(vref, name)
    return vref
end
```

# Constraint

```
struct StructuredConstraintRef
    model::StructuredModel
    idx::Int
end
function JuMP.add_constraint(
    model::StructuredModel, c::JuMP.AbstractConstraint,
    name::String="")
    model.nextconidx += 1
    cref = StructuredConstraintRef(
        model, model.nextconidx)
    model.constraints[cref.idx] = c
    JuMP.set_name(cref, name)
    return cref
end
```

# Objective

```
function JuMP.set_objective_sense(  
    model::StructuredModel, sense::MOI.OptimizationSense)  
    model.objective_sense = sense  
end  
  
function JuMP.set_objective_sense(  
    model::StructuredModel, f::JuMP.AbstractJuMPScalar)  
    model.objective_function = f  
end
```

## New attribute

```
struct VariableBlock <: MOI.AbstractVariableAttribute  
end
```

- Block 0: parent
- Block  $i$ :  $i$ th children

```
optimizer = PIPS.Optimizer()  
parent_vars = MOI.add_variables(optimizer, n0)  
MOI.set(optimizer, VariableBlock(), parent_vars,  
         zeros(n0))  
child1_vars = MOI.add_variables(optimizer, n1)  
MOI.set(optimizer, VariableBlock(), child_vars,  
         zeros(n1))
```

## MomentOpt extension

---

## Example

Generalized Moment Problem for

$$\min_{|x| \leq 1, |y| \leq 1} x^4 y^2 + x^2 y^4 - 3x^2 y^2 + 1$$

```
@polyvar x y
f =x^4*y^2 + x^2*y^4 -3x^2*y^2 + 1
K = @set -1 <= x && x <= 1 && -1 <= y && y <= 1
gmp = GMPModel()
@measure(gmp, mu, [x, y], support=K)
@objective(gmp, Min, dot(f, mu))
@constraint(gmp, dot(1, mu) == 1)
relax!(gmp, 2, with_optimizer(CSDP.Optimizer))
```

```
mutable struct GMPModel <: JuMP.AbstractModel
    objective::Union{Nothing, MomObj}
    constraints::Vector{MomCon}
    constraint_names::Vector{String}
    measures::Vector{Measure}

    dual::JuMP.Model
    cref::Dict{Measure, JuMP.ConstraintRef{JuMP.Model}}
    dref::Vector{JuMP.VariableRef}
end
```

# Constraint

```
function JuMP.build_constraint(  
    _error::Function, aff::AffMomExpr,  
    set::MOI.AbstractScalarSet)  
    return MomCon(aff, set)  
end
```

```
function JuMP.add_constraint(  
    gmp::GMPModel, momcon::MomCon, name::String="")  
    push!(gmp.constraints, momcon)  
    push!(gmp.constraint_names, name)  
    return ConstraintRef(gmp, length(constraints(gmp)),  
                        MomConShape())  
end
```

# Objective

```
function JuMP.set_objective(  
    gmp::GMPModel, sense::MOI.OptimizationSense,  
    mom::AbstractMomentExpressionLike)  
    gmp.objective = MomObj(sense, mom)  
end
```

```
function relax!(gmp::GMPModel, order::Int,  
                optimizer::OptimizerFactory)  
    gmp.dual = SOSModel(optimizer)  
  
    # ...  
  
    optimize!(gmp.dual)  
end
```

Many ways to extend JuMP/MOI:

- Create new MOI attribute/submittable
- Create new MOI set and bridge
- Create new `AbstractVariableRef`
- Extend variable macro with `parse_variable`, `build_variable`, `add_variable`
- Extend constraint macro with `parse_constraint`, `build_constraint`, `add_constraint`
- Extend objective macro with `set_objective_function`
- Use the `ext` field and an optimize hook
- Use a custom `JuMP.AbstractModel`
- ...