

Set Programming with JuMP

Benoît Legat*, *In collaboration with:* Raphaël M. Jungers*, Pablo A. Parrilo[†] and Paulo Tabuada[‡]

* UCLouvain, [†] MIT, [‡] UCLA

Set program

Set inclusion

Consider two sets $S \subseteq \mathbb{R}^n$, $T \subseteq \mathbb{R}^m$, matrices $A \in \mathbb{R}^{r \times n}$, $B \in \mathbb{R}^{r \times m}$:

$$AS \subseteq BT.$$

Set program

Given fixed sets T_i , find sets S_i :


$$\max_{S_i, x_i} f(\text{vol}(S_1), \dots, \text{vol}(S_n))$$

$$A_j S_{a_j} \subseteq B_j S_{b_j}$$

$$S_i \subseteq T_i$$

$$x_{c_j} \in S_{d_j}$$

Stability of Hybrid Systems




Instability may be certified using a **low-rank** infeasibility certificate.

See presentation at *19th ACM International Conference on Hybrid Systems: Computation and Control*, (HSCC), 2016.





See presentation at *37rd Symposium on Information Theory in the Benelux*, 2016.

Safe Model Predictive Control



See presentation at *IFAC Conference on Analysis and Design of Hybrid Systems (ADHS)*, 2018.



See presentation at *23rd International Symposium on Mathematical Programming (ISMP)*, 2018.

Example with ellipsoids: Model


Maximal volume ellipsoid (determinant):

```
model = Model(...)
@variable(model, S, Ellipsoid(symmetric=true))
@constraint(model, S ⊆ □)
@constraint(model, A * S ⊆ E * S)
@objective(model, Max, nth_root(volume(S)))
@time JuMP.optimize!(model)
ell = □ JuMP.value(S)
```


Maximal sum of the squares of the semi-axes of the ellipsoid (trace):

```
@objective(model, Max,
            L1_heuristic(volume(S), [1.0, 1.0]))
```

Example with ellipsoids: Primal Solution



Example with ellipsoids: Polar Solution




Example with polynomial sublevel set: Model


```
@variable(model, S, PolySet(degree=d, convex=true,  
                             symmetric=true))
```

Use L1 norm as volume heuristic.

Example with polynomial sublevel set: Primal Solution



Example with polynomial sublevel set: Polar Solution



Set variables

```
function JuMP.build_variable(  
    _error, info::JuMP.VariableInfo, set::AbstractSetVariable  
    if info.has_lb || info.has_ub || info.has_fix ||  
        info.binary || info.integer || info.has_start  
        _error(...)  
    end  
    return set  
end  
function JuMP.add_variable(  
    model::JuMP.AbstractModel, set::AbstractSetVariable,  
    name::String)  
    vref = SetVariableRef(...)  
    push!(data(model).variables, vref)  
    return vref  
end
```

Parsing set constraints

```
function JuMP.parse_one_operator_constraint(_error::Function, vectorized::Bool,  
                                           ::Val{:<}, lhs, rhs)  
    _error("Unrecognized symbol < you mean ≤ ?")  
end  
function JuMP.parse_one_operator_constraint(_error::Function, vectorized::Bool,  
                                           ::Val{:<}, lhs, rhs)  
    parse_code = :()  
    if vectorized  
        build_call = :(JuMP.build_constraint($_error, $(esc(lhs)), $(esc(:(SetProg.PowerSet($rhs))))))  
    else  
        build_call = :(JuMP.build_constraint($_error, $(esc(lhs)), $(esc(:(SetProg.PowerSet($rhs))))))  
    end  
    return parse_code, build_call  
end  
function JuMP.parse_one_operator_constraint(_error::Function, vectorized::Bool,  
                                           ::Val{>}, lhs, rhs)  
    _error("Unrecognized symbol >, did you mean ≥ ?")  
end  
function JuMP.parse_one_operator_constraint(_error::Function, vectorized::Bool,  
                                           ::Val{>}, lhs, rhs)  
    parse_one_operator_constraint(_error, vectorized, Val{<}, rhs, lhs)  
end
```

Store set constraints

```
function JuMP.build_constraint(  
    _error::Function, subset, sup_powerset::PowerSet;  
    kws...)   
    InclusionConstraint(subset, sup_powerset.set, kws)  
end  
function JuMP.add_constraint(  
    model::JuMP.Model, constraint::SetConstraint,  
    name::String="")  
    d = data(model)  
    index = ConstraintIndex(d.last_index += 1)  
    d.constraints[index] = constraint  
    d.names[index] = name  
    return JuMP.ConstraintRef(model, index, SetShape())  
end
```

Optimize hook

create_spaces: Find dimensions and representation (e.g. polar/dual or not)

```
function optimize_hook(model::JuMP.AbstractModel)
    d = data(model)
    clear_spaces(d)
    create_spaces(d)
    load(model, d)
    JuMP.optimize!(model, ignore_optimize_hook = true)
end
```

Load set constraints

S-procedure:

$$\begin{aligned} Q &\subseteq P \\ x^\top Q x \leq 1 &\Rightarrow x^\top P x \leq 1 \\ x^\top P x &\leq x^\top Q x \quad \forall x \\ Q - P &\text{ is PSD} \end{aligned}$$

```
function JuMP.build_constraint(  
    _error::Function, subset::Ellipsoid,  
    sup_powerset::PowerSet{<:Ellipsoid})  
    Q = subset.Q  
    P = sup_powerset.set.Q  
    JuMP.build_constraint(_error, Symmetric(Q - P),  
        PSDCone())  
end
```

Polar inclusion

```
function JuMP.build_constraint(  
    _error::Function, subset::Sets.Polar,  
    sup_powerset::PowerSet{<:Sets.Polar})  
    S = subset  
    T = sup_powerset.set  
    JuMP.build_constraint(  
        _error, Sets.polar(T), PowerSet(Sets.polar(S)))  
end  
  
function JuMP.build_constraint(  
    _error::Function, subset::Sets.Polar,  
    sup_powerset::PowerSet{<:Polyhedra.HalfSpace})  
    point = sup_powerset.set.a / sup_powerset.set.b  
    JuMP.build_constraint(_error, point, Sets.polar(subset))  
end
```

- Rely on `MathematicalSets` to represent sets.
- Polyhedra solver (CDD, LazySets, ...)
- Direction objective: Ellipsoid (SDP), polynomial (SOS), polyhedra (SDDP).